



مصنع دانة لوبريكانتس (ذ م م)  
DANA LUBRICANTS FACTORY L.L.C  
(A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

## SAE 10W40 API SN DANA GOLD GASOLINE ENGINE OIL WITH 10000 KM PLUS Warranty (FULLY SYNTHETIC OIL)

**Performance Standard: API SN**

**Manufacturer: DANA Lubricants Factory LLC, UAE**

**SAE 10W40 API SN GASOLINE ENGINE OIL** is a special formulation using synthetic lubricant base oil technology suitable for modern passenger car gasoline engine oil exceeding the performance Specification API SN. Developed to provide maximum protection for modern passenger car, including low emission engine and high performance vehicles. It is available 10W40 API SN viscosity grade to provide fuel saving and to meet long drain requirements. Compatible for all cars running on lead free gasoline and catalytic converters

### EVO

E- Extra Protection to Engine, Clutch & Gears

V- Value for Money with 70% Extra Mileage

O- Outstanding Performance in all Weathers

### SPECS

-Meets or exceeds the requirements of Dana EVO gasoline engine oil

Features	Advantages
Broad Viscosity Range	Superior protection an performance in all weather conditions throughout year
Good Anti Wear Properties	Extends Engine Life
High Thermal Stability & Oxidation Stability	Keeps Engine Clean for smoother operation
Good Corrosion Protection	Protects engine components for long time
Advanced detergency leading to cleaner engines and longer component life.	Excellent Wet clutch performance



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: [danalubes@danagroups.com](mailto:danalubes@danagroups.com), [www.danalubes.com](http://www.danalubes.com)

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , [www.danagroups.com](http://www.danagroups.com)



مصنع دانة لوبريكانتس (ذ م م)  
DANA LUBRICANTS FACTORY L.L.C  
(A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

#### Performance Levels:

- API SN
- ILSAC GF-5
- FORD WSS-M2C946-A
- GM 6094M
- BMW Special Oil

**Always follow equipment manufacturer's recommendation for the required lubricant performance level and oil drain interval.**

#### Typical Properties:

SAE Grade	10w40
Appearance	B&C
Viscosity @40 °C ASTM D 445, CST	102.35
Viscosity @100 °C ASTM D 445, CST	14.98
Viscosity Index ASTM D 2270	154
Flash Point, COC ASTM D 92	225
Pour Point, °C ASTM D97	-39
Density @ 15 °C ASTM D 4052	0.87
TBN (mg KOH/gm) ASTM D 2896	8.8
Sulphated Ash, WT % , ASTM D874	<1.0
CCS , CP, ASTM D5293	6600@ -25 °C
Volatility, % off @ 250 °C ASTM D5800	10-12 max

#### Handling, Health and Safety

Lubricant consisting of highly refined mineral oils with specific additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: [danalubes@danagroups.com](mailto:danalubes@danagroups.com), [www.danalubes.com](http://www.danalubes.com)

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , [www.danagroups.com](http://www.danagroups.com)