



مصنع دانة لوبريكانتس (ذ م م)
DANA LUBRICANTS FACTORY L.L.C
(A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

DANA GOLD INDUSTRIAL GEAR OIL

Manufacturer: DANA Lubricants Factory LLC, UAE

DANA GOLD INDUSTRIAL GEAR OIL is high performance synthetic gear lubricant with special additives to enhance their anti-oxidation and anti-corrosion characteristics. These oils are produced to meet major OEM requirements which include GM, MAN, DAVID BROWN etc. These oils can be used in industrial high-speed/shock-loaded gears. Also they can be used in plastic calendars where high bulk oil temperatures of up to 200°C may be experienced.

EVO

- Excellent protection against wearing & scoring produced by high speed & heavy load.
- Formulated for automotive high speed gear
- Suitable for wide variety of application & services Condition.

SPECS

-Meets or exceeds the requirements of Dana gold industrial gear oil

Features	Advantages
Broad Viscosity Range	Superior protection against rusting pitting & corrosion.
Good Anti Wear Properties	Suitable for wide variety of application & services Condition.
High Thermal Stability & Oxidation Stability	Compatible with seals and gaskets.
Good Corrosion Protection	Excellent lubrication without channeling at low temperature.
Advanced detergency leading to cleaner engines and longer component life.	Excellent load carrying capacity and good antifoam properties.



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: danalubes@danagroups.com, www.danalubes.com

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , www.danagroups.com



مصنع دانة لوبريكانتس (ذ م م)
DANA LUBRICANTS FACTORY L.L.C
(A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

Performance Levels:

AISE	224
AGMA	9005-E02
DIN	51517 Part III
David Brown	S1.53.101

Always follow equipment manufacturer's recommendation for the required lubricant performance level and oil drain interval.

Typical Properties:

TEST	METHOD	UNITS	RESULT						
			68	100	150	220	320	460	680
ISO Grades			68	100	150	220	320	460	680
Kinematic Viscosity @ 40°C	ASTM D7042	Cst	68	100	150	220	320	460	680
Kinematic Viscosity @ 100°C	ASTM D7042	Cst	8.655	11.25	14.80	18.75	23.90	30.35	35.85
Viscosity Index	ASTM D2270	-	98	98	98	95	95	95	85
Pour Point	ASTM D97	°C	-24	-24	-21	-18	-15	-12	-9
Flash Point COC	ASTM D92	°C	230	235	235	235	235	235	240
Density at 15 °C	ASTM D4052	kg/l	0.886	0.89	0.892	0.894	0.896	0.898	0.901



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: danalubes@danagroups.com, www.danalubes.com

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , www.danagroups.com



مصنع دانة لوبريكانتس (ذ م م)
DANA LUBRICANTS FACTORY L.L.C
(A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

Handling, Health and Safety

Lubricant consisting of highly refined mineral oils with specific additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: danalubes@danagroups.com, www.danalubes.com

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , www.danagroups.com