



مصنع دانة لوبريكانتس (ذ م م)
DANA LUBRICANTS FACTORY L.L.C
(A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

SAE 10W40 API SL JASO MA2 DANA PREMIUM 4T ENGINE OIL WITH 5000 KM PLUS Warranty (MADE FROM 100% VIRGIN OIL)

Performance Standard: API SL JASO MA2

Manufacturer: DANA Lubricants Factory LLC, UAE

SAE 10W-40 API SL JASO MA2 DANA PREMIUM 4T ENGINE OIL is a high performance conventional four-stroke motorcycle engine oil primarily intended for general **use in all types of four-stroke motorcycles** and engines. SAE 10W40 API SL JASO MA2 DANA PREMIUM 4T ENGINE OIL combines highly refined mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection.

Note: 4T 10W40 is recommended to be used in motorcycles and engines as per manufacturers recommendation

EVO

- E- Extra Protection to Engine, Clutch & Gears
- V- Value for Money with 70% Extra Mileage
- O- Outstanding Performance in all Weathers

SPECS

-Meets or exceeds the requirements of Dana EVO 4T ENGINE OIL

Features	Advantages
Broad Viscosity Range	Superior protection an performance in all weather conditions throughout year
Good Anti Wear Properties	Extends Engine Life
High Thermal Stability & Oxidation Stability	Keeps Engine Clean for smoother operation
Good Corrosion Protection	Protects engine components for long time
Advanced detergency leading to cleaner engines and longer component life.	Excellent Wet clutch performance



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: danalubes@danagroups.com, www.danalubes.com

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , www.danagroups.com



مصنع دانة لوبريكانتس (ذ م م)
DANA LUBRICANTS FACTORY L.L.C
(A Division of DANA Group)



ISO9001:2008
Registered company by IIC (No: JU- 1306)

Performance Levels:

- API JASO MA2

Always follow equipment manufacturer's recommendation for the required lubricant performance level and oil drain interval.

Typical Properties:

SAE Grade	10W40
Appearance	B&C
Viscosity @40 °C ASTM D 445, CST	105.28
Viscosity @100 °C ASTM D 445, CST	14.23
Viscosity Index ASTM D 2270	137
Flash Point, COC ASTM D 92	220
Pour Point, °C ASTM D97	-24
Density @ 15 °C ASTM D 4052	0.89
Sulphated Ash, WT % , ASTM D874	<1.0
CCS , CP, ASTM D5293	6900@ -25 °C
Volatility, % off @ 250 °C ASTM D5800	12-14 max

Handling, Health and Safety

Lubricant consisting of highly refined mineral oils with specific additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: danalubes@danagroups.com, www.danalubes.com

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , www.danagroups.com